


Series 4, Gas hob, 60 cm, Tempered glass, Black PNP6B6K40



Optional accessories

HEZ32WA00	Wireless food thermometer
HEZ9SE040	4 pieces Set

The gas hob with dishwasher suitable cast iron pan supports, Ergonomic sword dials, and a Main Switch for precise control.

- **Ergonomic sword dials:** with raised center for precise adjustments.
- **Tempered Glass:** for strength and aesthetic.
- **Dishwasher-suitable pan supports:** Easy, scrub-free cleaning.
- **Semi-continuous pan supports:** smaller for easy cleaning, yet providing a seamless cooking surface.
- **Safety gas cut-off:** ensures safety by instantly cutting off gas supply if the flame goes out.

Technical Data

Appliance type:	 gas hob w integrated controls
Built-in / Free-standing:	 Built-in
Heating type:	 Gas
Number of cooking zones:	 4
Type of control setting devices:	 sword knobs
Required niche size for installation (HxWxD):	45 x 560-560 x 480-490 mm
Width of the appliance:	 590 mm
Dimensions:	 45x590x520 mm
Dimensions of the packed product (HxWxD):	 150x660x580 mm
Net weight:	 15.9 kg
Gross weight:	 17.1 kg
Residual heat indicator:	 Without
Location of control panel:	 Front
Basic surface material:	 Tempered glass
Color of surface:	 Black
Color of frame:	 Black
Length electrical supply cord:	 100 cm
EAN code:	 4242005437856
Gas connection rating:	 7500 W
Fuse protection:	 3 A
Voltage:	 220-240 V
Frequency:	 50; 60 Hz



Series 4, Gas hob, 60 cm, Tempered glass, Black PNP6B6K40

The gas hob with dishwasher suitable cast iron pan supports, Ergonomic sword dials, and a Main Switch for precise control.

Design

- Tempered glass surface, Black
- Cast iron pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 gas burners:
- Left front: standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: high-speed burner up to 3 KW (depending on gas type)
- Right front: economy burner up to 1 KW (depending on gas type)

Cleaning

- Dishwasher suitable pan supports for easy cleaning.
- Cast iron pan supports with rubber feet: little weight and compact form, yet high stability due to continuous surface.

Safety


- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU)
- Natural gas L 25 mbar (NL)
- Liquid gas G30,31 28-30/37mbar
- Liquid gas G30 37 mbar (PL)
- Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 57.4 x 590 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 490)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 7.5 KW
- frameless design: install the hob either flush or slightly raised on the worktop
- If installed flush, minimum worktop thickness is 30mm.

Series 4, Gas hob, 60 cm, Tempered glass, Black PNP6B6K40

Measurements in mm



A: Min. distance from the hob cut-out to the wall

B: Position of gas connection in the cut-out

C: With fitted oven underneath possibly more; see space requirements for the oven

For worktop thickness between 12 mm to 20 mm need additional spacer, contact customer service for details