



GW452120

Included accessories

1 x grid

warming drawer Gaggenau Expressive series
60 x 28 cm, Stainless steel behind smoked glass
GW452120

- Handleless opening with a light push for convenience and style
- Seamlessly integrated with multiple Gaggenau appliances, offering flexibility and a harmonious aesthetics
- Hygienic stainless steel and glass interior for effortless cleaning and elegant design
- Second-level grid adds space, making the warming drawer more versatile and efficient
- Six power levels and four heating modes ensure consistent temperature control for various culinary needs

Highlights

Handleless drawer

Bright interior lighting.

Push-to-open function.

Hygienic stainless steel interior with glass bottom

Direct temperature selection in the range 30 °C to 80 °C.

Also for low-temperature cooking, dough proving, herbs and fruits drying, chocolate melting and defrosting.

Heating methods

Preheating of small beverage containers.

Warming ovenware.

Keeping meals warm.

Low-temperature cooking.

Direct temperature control.

Personalisation function via Home Connect.

16 additional programmes via Home Connect.

Handling

Touch key operation.

Features

Net volume 52 litres.

Additional grid creates a second level and extends storage space.

Volume capacity: Dinner service for 12 people including ø 27 cm plates and soup bowls, additional bowls and a serving dish depending on size.

Capacity load max. 25 kg.

Usable interior dimensions

W 548 mm x H 232 mm x D 410 mm.

Heating system for even heat distribution and stable cavity temperature.

Status indicator, visible on the frame.

Glass bottom made of safety glass.

Selected digital services (Gaggenau Home Connect)

Additional programmes and recipes.

Remote control and monitoring.

Planning notes

Plan the niche without back wall.

Protrusion from appliance front to furniture cabinet 42 mm.

Installation of GO/GS/GM/GC directly above the drawer without intermediate shelf.


Drawers installed above a dishwasher need a specific niche.

The socket can be planned behind the appliance.

Connection

Total connected load 0.82 KW.

Connection cable 1.75 m, pluggable.



A: Accessible electrical connection

Measurements in mm